

900 SERIES LIQUID-COOLED FRONTMOUNT™

Our ultimate FrontMount™ performer.



IT'S SO MUCH MOWER®



- With more power, durability and maneuverability than any mower in its class, our 900 Series power units are equipped with powerful, clean-burning engines that allow you to muscle your way through all conditions. Models 930D and 932 are perfect for fleet operations, combining True ZeroTurn™ maneuverability with a quality cut and versatile performance.
- Durable, design-matched hydrostatic transmissions with CoolFan™ hydro cooling system provide smoother response and less maintenance with 1,000-hour fluid change intervals.
- Excellent weight distribution provides a smoother ride and lighter footprint. A standard hydraulic deck lift simplifies implement operation and transport.
- Each DuraMax® deck easily converts from wide-pattern side discharge to optional mulching or vacuum collection.



Forward speeds up to 11 mph – or up to 7.19 acres per hour – make quick work of large acreage applications.

Model 932

- 32 hp, 3-cylinder liquid-cooled Kubota MaxTorque™ gasoline engine
- Rugged G2 transmission with CoolFan™ hydro cooling system and 7 micron absolute filter
- 52-, 61- or 72-inch DuraMax® decks

Standard Features for 900 Series

- Powerful, liquid-cooled, OHV engines with horizontal crankshaft and pressure lube for smooth, reliable operation
- Heavy-duty, remote-mounted air cleaner with replaceable element and filter minder
- Interchangeable DuraMax® decks with anvil-edged design for exceptional durability
- CoolTemp Cordura® Ultimate Suspension Ride™ (USR™) seat with embroidered logo, lumbar support and adjustable armrests
- Hydraulic deck lift with switch in lever
- QuikAjust Tilt™ “no tools” lever adjustment with 9-inch comfort range
- Temperature sentry/high temperature clutch cut-out
- Halogen work lights
- 8-gallon fuel tank for additional mowing capacity on 930D
- Adjustable cup holder
- Bar tread, low-pressure tires
- Wide-stance, single-fork tail wheels
- ROPS with adjustable seat belt
- Hour meter
- QuikConverter™ implement-capability

Model 930D

Clean Diesel

ig system

**THIS MODEL
IS
NO LONGER AVAILABLE**

Options for 900 Series

- PowerFold® for 52- and 61-inch DuraMax® decks (standard on 72-inch decks)
- Height adjustment switch on armrest for PowerFold®
- Quik-D-Tatch® PowerVac™ Collection Systems
- Down Discharge™ mulching packages
- Dedicated rear-discharge decks
- Extended steering levers
- Big Boy wide-seat conversion kit
- Premier suspension seat
- Full-flotation deck feature
- Speed-Trimming™ heavy-duty, anti-scalp roller
- Turf tires
- Dual-fork and wide-stance, dual-fork tail wheels
- Foldable ROPS with adjustable seat belt
- QuikConverter™ implements
- Yellow beacon light
- Radiator Cleaning Wand

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment.

Liquid-Cooled 900 Series FrontMount™ Specifications

MODEL	930D	932
ENGINE		
Type/Horsepower*/Cylinders	Hyundai 12-cyl.	Kubota MaxTorque™/32 hp/3-cyl.
Displacement		58.7 cu. in. (962 cc)
Crankshaft /Lubrication System		Horizontal/Pressure Lube, Filter
Fuel		Gasoline - unleaded
Fuel Capacity		7.2 gal. (27.3 l)
Air Filter		3 dual air cleaner with replaceable element and filter minder.
Muffler		Quiet, single, industrial type.
DECK COMPATIBILITY		
52-inch		
61-inch		
72-inch		
STARTER & ELECTRICAL SYSTEM		
Maintenance-Free Battery/Starter		12 Volt/solenoid shift
Ignition		Breakerless
Interlock Switch		Clutch is engaged or steering levers are in drive position. Own only when PTO is disengaged and steering levers are locked in neutral.
ULTIMATE OPERATOR STATION™		
Seat - USR™		Cordura-covered, folding padded armrests and padded backrest with lumbar support. Embroidered logo. Optional Premier suspension seat.
Suspension		InFrame™ suspension
Console-Mounted Instruments	Oil engine	meter, Oil, alternator, temp. & parking brake warning lights, hour meter, engine temp.
Work Lights		5 switches. & volt gauges, work light & ignition switches, choke & push/pull PTO switch.
TRANSMISSION & STEERING		Standard - Halogen
Type	Design	15, HydroGear variable displacement piston-type pumps and high-torque Parker wheel motors.
Transmission Fluid		stands high and low temperature extremes for 1,000-hour change intervals.
Filtration		7 micron absolute, spin-on
Speed		0 - 11.0 mph (0 - 17.7 kph) forward 0 - 6.0 mph (0 - 9.7 kph) reverse
Turning Radius		With counter-rotating, independently powered drive wheels. Seat is pivot point.
Steering		With™ dual levers that automatically return to neutral from either forward or reverse position.
Brakes		Static transmission/disc parking brakes, one for each drive wheel.
Attachment Drive		Ints, Quik-D-Tatch® coupler and heavy-duty electric Mag Stop® blade clutch/brake.
POWER UNIT TIRE SIZE		
Drive Wheels (4-ply rated)	22x11.00x10 bar tread, high flotation	22x11.00x10 bar tread, high flotation
Drive Wheel Options (4-ply rated)	22x10.00x10, turf tread	22x10.00x10, turf tread
Wide-Stance, Single Tail Wheel	13x6.50x6 rib tread, pneumatic (2)	13x6.50x6 rib tread, pneumatic (2)
POWER UNIT DIMENSIONS		
Width	53.0 in. (134.6 cm)	53.0 in. (134.6 cm)
Length	70.0 in. (177.8 cm)	70.0 in. (177.8 cm)
Height (ROPS)	69.0 in. (175.3 cm)	69.0 in. (175.3 cm)
Height (Seat back/Seat cushion)	46.5 in. (118.1 cm)/31.0 in. (78.7 cm)	46.5 in. (118.1 cm)/31.0 in. (78.7 cm)
Wheelbase	54.5 in. (138.4 cm)	54.5 in. (138.4 cm)
WEIGHT		
Uncrated	1150 lbs. (521.6 kg)	1100 lbs. (499.0 kg)

**THIS
MODEL
IS
NO
LONGER
AVAILABLE**

* All power levels are stated gross horsepower at 3600 RPM as rated by the engine manufacturer.

DuraMax® Decks for 900 Series FrontMount™ Models

WIDTH OF CUT	52 in. (132.1 cm)	61 in. (154.9 cm)	72 in. (182.9 cm)
COMPATIBILITY		All 900 Series Models	
DECK MODEL	3452	3461	3472
WIDTH w/DEFLECTOR	65.5 in. (166.5 cm)	74.5 in. (189.2 cm)	85.5 in. (227.3 cm)
WIDTH (MULCHING)	53.5 in. (135.9 cm)	62.5 in. (158.8 cm)	73.5 in. (186.7 cm)
CUTTING HEIGHT		1.0 to 5.0 in. (2.5 cm to 12.7 cm)	
POWERFOLD® OPTION	YES	YES	Standard
CONSTRUCTION	Tubular 2.25 in. x 4 in. boxed members with 0.25 in. gussets. Formed double thickness steel (0.269 in. > heavier than 3 gauge) truss spindle plane and (3) Sentry™ spindles with 8-inch spindle flanges, with 6-bolt pattern and a triple-strength upper deck, 0.9 in. thick in stress zones for superior strength. Geometrically engineered design with 7-gauge skirts withstands the brunt of commercial mowing.		
BLADES*	(3) 18 in. (45.7 cm)	(3) 21 in. (53.3 cm)	(3) 25 in. (63.5 cm)
SPINDLE ASSEMBLIES	2.5 cm (approx. 1 in.) O.D. shaft. Double bearing. Greasable from top of deck. Deck spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion. Machined aluminum alloy housing. Maintenance-free gearbox with single Kevlar V-belt and idler arm tensioning.		
BLADE DRIVE			
TRIMABILITY (Outside of tire to left trim side)	-.05 in. (-1.3 cm)	7.0 in. (17.8 cm)	12.25 in. (31.1 cm)
POWER UNIT/DECK LENGTH			
DECK (mowing position)	108.5 in. (275.6 cm)	110.5 in. (280.7 cm)	120.5 in. (306.1 cm)
DECK (folded up)	91.5 in. (232.4 cm)	94.0 in. (238.8 cm)	107.0 in. (271.8 cm)
TIRE SIZE (4-ply rated)	9 x 3.50 x 4 (flat-proof)		
WEIGHT UNCRAVED			
SIDE DISCHARGE	370 lbs. (167.8 kg)	420 lbs. (190.5 kg)	545 lbs. (247.2 kg)
Mulching Package**/Order #	29 lbs. (13.2 kg)/504567	36 lbs. (16.3 kg)/504569	44 lbs. (20.0 kg)/504571

- * High-lift blades standard.
- ** Package includes high-low mulching blades.

All specifications and information contained herein are subject to change without notice. CoolFan, Down Discharge, FrontMount, Hydra-Smooth, Hydro-Max, InFrame, MaxTorque, PowerVac, QuikAdjust Tilt, QuikConverter, Sentry, Speed-Trimming, True ZeroTurn, Ultimate Operator Station, Ultimate Suspension Ride and USR are trademarks and Grasshopper, the Grasshopper logo, DuraMax, It's So Much Mower, PowerFold and Quik-D-Tatch are registered trademarks of The Grasshopper Company. All other products are trademarks or registered trademarks of their respective holders.



IT'S SO MUCH MOWER®

The Grasshopper Company
One Grasshopper Trail • P.O. Box 637
Moundridge, KS • 67107 U.S.A.

T: 620-345-8621 • F: 620-345-2301

grasshoppermower.com

Litho in U.S.A. Form 0613-170554 © 2013 The Grasshopper Company



Paper contains 10% post-consumer content. 100% recyclable. Check for recycling programs in your area.